

Rebel™ EMP 205ic AC/DC

Specifications	
Primary Voltage	120/230 VAC 1 ph +/- 10%, 50/60 Hz
Input Current Draw	30 A (29.6 A) @ 25% Duty Cycle
Maximum Output	235 A / 26.0 V (MIG) 180 A / 27.2 V (MMA) 205 A / 18.2 V (DC TIG)
MIG (GMAW/FCAW) Welding Output	205 A / 24.3 V @ 25% Duty Cycle 150 A / 21.5 V @ 40% Duty Cycle 125 A / 20.3 V @ 60% Duty Cycle 110 A / 19.5 V @ 100% Duty Cycle
MMA (SMAW) Welding Output	170 A / 26.8 V @ 25% Duty Cycle 125 A / 25.0 V @ 60% Duty Cycle 100 A / 24.0 V @ 100% Duty Cycle
TIG (GTAW) AC/DC Welding Output	205 A / 18.2 V @ 25% Duty Cycle 125 A / 15.0 V @ 60% Duty Cycle 110 A / 14.4 V @ 100% Duty Cycle
AC TIG Functionality Balance Range Frequency Range	60 – 90% 25 – 400 Hz
DC TIG Functionality Pulsed TIG (DC only)	0.1 – 500 Hz
Current Range	5 – 235 A
MIG Welding Voltage Range	12 – 26 V
Wire Feed Speed Range	2.0 – 12.1 m/min
Open Circuit Voltage	68 V
Rated kVA	4.98 kVA (recommended > 7 kVA generator)
Power Factor at Max Current	0.98
Efficiency at Max Current	83%
Approvals	CE
Protection Class	IP23S
Dimensions, L x W x H	584 x 229 x 406 mm
Weight	25.5 kg

Ordering Information	
Rebel EMP 205ic AC/DC, CE	0700300998

Delivery includes: power source with 3 m mains cable and plug, MXL 201 MIG torch 3 m, SR-B 26 TIG torch w. accessories (3 collet 1.6-3.2 mm, 3 collet body 1.6-3.2 mm, 1 long back cap, 3 ceramic nozzles and 3 gold tungstens 1.6-3.2 mm), electrode holder, return cable and clamp 3 m, gas hose with quick connector 4.5 m, drive rolls for 0.6, 0.8 and 1.0 mm wire, guide tubes 0.6-1.2 mm, thickness gauge tool

Options & Accessories	
TIG Foot Control 4.5 m cable and 8-pin connector	W4014450
2-wheel trolley	0700300872
SR-B 26 TIG Torch, Gas, OKC50, 4 m	0700025580
SR-B 26 TIG Torch, Gas, OKC50, 8 m	0700025581
SR-B 26FX-R TIG Torch, Gas, OKC50, flex head, remote, 4 m	0700025589
SR-B 26FX-R TIG Torch, Gas, OKC50, flex head, remote, 8 m	0700025590
MXL 201 Gas-cooled MIG Torch with Euro Connection, 3 m	0700025220
Handy 200 Electrode Holder	0700006003